

SIRENA

MG-LED-046-400



Specification:

1.LED Quantity:30pcs/40pcs 3030	7.Color Rendering Index: > 70	13.Diffuser:Frosted ,Prismatic,Clear PMMA
2.Power:30W/40W	8.LED Efficiency:100LM/W	14.IP Rate: IP65
3.Input Voltage:100-240V/277V	9.Luminous Flux:3000LM/4000LM	15.Humidity:10%-90%
4.Frequency Range:50-60HZ	10.Work Temperature:-30°C-60°C	16.LED Life: > 50000h
5.Power Factor: > 0.9	11.Installation pole dia:60MM	
6.Color Temperature:2700-6500K	12.Material: Die casting Aluminum Alloy	



SIRENA

MG-LED-046-500



A




B



C



D



Specification:

1.LED Quantity:50pcs/60pcs/80pcs 3030	7.Color Rendering Index: > 70	12.Material: Die casting Aluminum Alloy
2.Power:50W/60W/80W	8.LED Efficiency:100LM/W	13.Diffuser:Frosted ,Prismatic, Clear PMMA
3.Input Voltage:100-240V/277V	9.Luminous Flux:5000LM/6000LM /8000LM	14.IP Rate: IP65
4.Frequency Range:50-60HZ	10.Work Temperature:-30°C-60°C	15.Humidity:10%-90%
5.Power Factor: > 0.9	11.Installation pole dia:60MM	16.LED Life: > 50000h
6.Color Temperature:2700-6500K		

